date projectname attn from fax

email phone 11-8-16 We Olive Eric eric

8015054262

ericr@mwciutah.com

8015054262



U6054

Uni-Door Folded Towel & Waste Combination Unit

	JOB #:
	ITEM #:
	OLIANTITY:

Revision 05/11

MOUNTING	HANDING	TYPE	SIZE	OTHER	
17 1/2" 444mm 15 1/4" 387mm	18" 457mm — Ç 54 1/4" 1378mm — 26" 660mm	1/2" 13mm ADJ BACK	58" - 62" (1473 mm - 1575 mm) RECOMMENDED MOUNTING HEIGHT	6 1/4 " 159mm -S4 4 1/4" 108mm ADJ. BACK -S2 2 1/4" 57mm	

SPECIFICATIONS

Body: Fabricated of #22 ga stainless steel with a #4 satin finish.

Flange: Fabricated of #22 ga stainless steel with a #4 satin finish and 1/4" returns to wall, no miters or welds.

Back: Fabricated of stainless steel formed for rigidity with multiple welds to cabinet body.

Door: Fabricated of #22 ga stainless steel with a #4 satin finish and full length door stops.

Towel Dispenser: Dispensing area has hemmed edges to prevent injury and towel tearing. Adjustable back allows c-fold and single-fold towels to be dispensed.

Dispenser: Dispensing area has hemmed edges to prevent injury and towel tearing.

Removable Waste Capacity: Removable steel waste with heavy duty handle for easy servicing.

Hinges: Heavy duty, full length, stainless steel piano type hinge.

Locks: Pin tumbler commercial quality keyed like all other AJW cabinets.

Collars: Fabricated of #22 ga stainless steel finished to match cabinet

Overall Size: 17 1/2"W x 54 1/4"H x 6 1/4"D

445mm x 1378mm x 159mm

Wall Opening: 15 3/4"W x 52 1/2"H x 6"D

400mm x 1339mm x 152mm

U6054-S2: 2" semi-recessed. Collar, 4" (102mm) wall opening **U6054-S4:** 4" semi-recessed. Collar, 2" (51mm) wall opening

U6054-SM: Surface Mounted

Towel Capacity: 600 c-fold,800 multifold or 1200 singlefold.

Waste Capacity: 10 gallons (1.34 cu ft)

Options:

-VL1: Reusable vinyl liner

INSTALLATION

Coordinate installation with contractor and architect to avoid interference with pipes vents etc. Provide a rough wall opening 15 3/4"W x 52 1/2"H. Wall opening depth will depend on style mounting. If a collar is required, slip over back of unit. Remove waste & install unit in opening. Make sure cabinet will sit flush in wall and secure with proper fasteners per application. Install waste back into cabinet and load paper towels.

When cleaning cabinet, use a soft cloth, a non-abrasive or chloric solutions.

NOTES

Formerly Model #: U6544