

U671AW

Roll Towel & Waste Combination Unit

	JOB #:
	ITEM #:
	QUANTITY:

Revision 10/14

MOUNTING HAI	NDING	TYPE	SIZE	OTHER	
54" 1372mm	1"	4" s s s s s s s s s s s s s s s s s s s		9 1/4" 235mm 1/4" 6mm 102mm	S2 2" 51mm
	203	mm '			

SPECIFICATIONS

Body: Fabricated of #22 ga stainless steel with a #4 satin finish.

Flange: Fabricated of #22 ga stainless steel finished to match cabinet with 1/4" returns. (No miters or welds)

Cabinet Back: Fabricated of stainless steel formed for rigidity with multiple welds to cabinet body.

Cabinet Door: Fabricated of #18 ga stainless steel with #4 satin finish.

Towel Dispenser: Lever operated mechanism that requires less than 5 lbs of force to operate.

Removable Waste: #22 ga stainless steel #4 satin finish with all leading edges to have a radius. Unit is secured in place by a bottom bracket guide and top lock.

Hinge: Full length, heavy duty, stainless steel piano type hinge.

Locks: Pin tumbler commercial quality, keyed like all other AJW cabinets. **Collars:**Fabricated of #22 ga stainless steel, finished to match cabinet.

(Used when full recessing cannot be accomplished)

Overall Size: $17 \frac{1}{4}$ "W x 54"H x 12"D (minimum wall depth of 4" required)

Wall Opening: 15 3/4"W x 52 1/2"H x 4"D

400mm x 1334mm x 102mm

438mm x 1372mm x 305mm

U671AW-S2: semi-recessed. with 2" collar, 4" wall opening 102mm

U671AW-SM: Full surface mounted collar **Waste Capacity:** 18 gallons (2.4 cu ft.)

Towel Capacity: One standard size roll of 8" or 9" wide. (Use only non-

perforated towels). One stub roll up to 2 3/4" OD
*Recommended 600ft roll for best results.

INSTALLATION

Coordinate installation with architect and contractor to avoid interference with pipes, vents, etc. Provide a rough wall opening 15 3/4"W x 52 1/2"H. See chart for required wall depth. If collar is required, slide collar over the back before installing into wall. Remove waste from cabinet and mount unit plumb and true in opening with proper fasteners per application. After adjustment is complete secure cabinet door and waste receptacle.

When cleaning cabinet use a non abrasive non-chloric solution and wiped off with the grain of the cabinet.

NOTES

Formerly Model #: U651AW