

U626

Folded Towel & Waste Combination Unit

	JOB #:
	ITEM #:

QUANTITY:

Revision 03/11

MOUNTING	HANDING	TYPE	SIZE	OTHER
14 1/4" 362 mm 12 1/4" 311 mm	10 1/2" 267 mm		I 1/4" D8mm - SP	4 1/4" 108 mm
.;s. s	9 1/2" 241 mm		54-60" 1372-1524mm SECOMMENDED MOUNTING HEIGHT	

Removable Waste

SPECIFICATIONS

Body: Fabricated of #22 ga stainless steel with a #4 satin finish.

Flange: Fabricated of #22 ga stainless steel with #4 satin finish and 1/4" returns to wall. (No miters or welds)

Cabinet Back: Fabricated of stainless steel formed for rigidity with multiple welds to cabinet body.

Cabinet Door: Fabricated of #22 ga stainless steel with #4 satin finish with full length door stop to prevent vandalism

Towel Dispenser: Dispensing area has hemmed edges to prevent injury and towel tearing.

Removable Waste: Stainless steel removable waste hemmed edges and embossed tabs for liners.

Hinges: Heavy duty, full length, stainless steel piano type hinge.

Lock: Pin tumbler commercial quality keyed like all other AJW cabinets. **Collars**: Fabricated of #22 ga #4 satin finish stainless steel finished to

match cabinet body.

Overall Size: 14 1/4"W x 26"H x 4 1/4"D

362mm x 660mm x 108mm

Wall Opening: 12 3/4"W x 24 1/2"H x 4"D

324mm x 622mm x 102mm

U626-S2: semi-recessed with 2" collar, 2" wall open. 51mm)

U626-SM: Surface mounted with full skirt. **Towel Capacity:** 350 c-fold or 475 multifold **Waste Capacity:** 2 gallons (.27 cu ft)

Options:

-VL3: Reusable vinyl liner.

-TK: Twist lock in lieu of keyed lock.

INSTALLATION

Coordinate installation with contractor and architect to avoid interference with pipes vents etc. Provide a rough wall opening 12 3/4"W x 24 1/2"H. Wall opening depth will depend on style mounting. Remove waste in install unit in opening. Make sure cabinet will sit flush in wall and secure with proper fasteners per application. Install waste back into cabinet and load paper towels.

-S2

When cleaning cabinet, use a soft cloth, a non-abrasive or chloric solutions.

-SM

NOTES