

MOLINITING

U985-SM

Baby Changing Station

JOB #:
ITEM #:
QUANTITY:

Revision 10/14

UNTING	HANDING	TYPE	SIZE	OTHER
	2: 57	3 1/2" 99mm 2 3/4" 78mm 35 1/2" 902mm 9 1/4" 355mm	34" 864mm from floor	5 1/4" 133mm 63 1/2" 1,613mm from floor

SPECIFICATIONS

Body: Fabricated of high impact ABS polyethylene with radius leading edges that prevent injury. Material is odor resistant and easy to clean and available in grey. Base is concave formed to allow safe and easy changing. Molded graphics and brail to comply with ADA Guidelines.

Liner Dispenser: An integral part of body that is standard with each unit.

External Wrap: Fabricated of #18 ga stainless steel with a #4 satin finish. Wrap is reinforced with a full length steel on steel mechanism with #11 ga mounting plate.

Gas Shocks: Concealed gas spring actuators ensure a safe and smooth open and close motion.

Safety Straps: Snap lock fasteners to hold child securely in place. **Overall Size:** 22 1/4"W x 35 1/2"H x 5 1/4"D (closed) 29 3/4"D (open)

565mm x 902mm x 133mm (closed) 756mm (open)

Colors Available: Grey

INSTALLATION

Coordinate installation with architect or contractor to avoid interference with surrounding objects in and out of wall. Transfer mounting points to wall surface and make sure unit is level, secure with proper fasteners for each application. (Recommend a qualified carpenter to install unit) Unit can be lowered with one hand and into position with less than 5 lbs of force, without turning or twisting of wrist. Verify with local codes and type approach (forward or side) for proper mounting height above finished floor.

Unit should be cleaned once or more daily with a clean nylon brush and spray disinfectant.

When properly installed, baby changing stations comply with ASTM static load performance requirements.

NOTES

Formerly Model #: U945V-SS