date
projectname
attn
from
fax
email
phone

6/5/2019 rf pat pat



U601

Folded Towel & Waste Combination Unit

JOB #:
ITEM #:

QUANTITY:

Revision 03/11

MOUNTING HAI	NDING TYPE	SIZE	OTHER	
14 1/4" 362mm 12 1/4" 311mm 17" 432mm 432mm 26" 660mm		6 1/4" 159mm 1/4" 6 mm 8 CK 1321mm BACK 1524-1727mm RECOMMENDED MOUNTING HEIGHT	6 1/4 " 159mm ADJ. BACK	-S4 4 1/4" 108mm -S2 2 1/4" 57mm

SPECIFICATIONS

Body: Fabricated of #22 ga stainless steel with a #4 satin finish.

Flange: Fabricated of #22 ga stainless steel with #4 satin finish and 1/4" returns to wall, no miters or welds.

Cabinet Back: Fabricated of stainless steel formed for rigidity with multiple welds to cabinet body.

Cabinet Door: Fabricated of #22 ga stainless steel with #4 satin finish with full length door stop.

Towel Dispenser: Dispensing area has hemmed edges to prevent injury and towel tearing. Adjustable back allows c-fold and single-fold towels to be dispensed.

Removable Waste: Removable waste, with heavy duty handle for easy removal

Hinges: Heavy duty, full length, stainless steel piano type hinge.

 $\boldsymbol{\textbf{Lock}} : \mbox{Pin tumbler commercial quality keyed like all other AJW cabinets.}$

Collars: Fabricated of #22 ga #4 satin finish stainless steel finished to

match cabinet body

Overall Size: 14 1/4"W x 54"H x 6 1/4"D

362mm x 1372mm x 159mm

Wall Opening: 12 3/4"W x 52 1/2"H x 6"D

324mm x 1334mm x 152mm

U601-S2: semi-recessed with 2" collar 4" wall opening 102mm **U601-S4:** semi-recessed with 4" collar 2" wall opening 51mm

U601-SM: Surface mounted with full skirt.

Towel Capacity: 600 c-fold or 800 multifold Or 1200 singlefold

Waste Capacity: 6 gallons (.80 cu ft)

Options:

-P: Rigid plastic waste insert

INSTALLATION

Coordinate installation with contractor and architect to avoid interference with pipes vents etc. Provide a rough wall opening 12 3/4"W x 52 1/2"H. Wall opening depth will depend on style mounting. If a collar is required, slip over the back of the unit. Remove waste & install unit in opening. Make sure cabinet will sit flush in wall and secure with proper fasteners per application. Install waste back into cabinet and load paper towels.

When cleaning cabinet, use a soft cloth, a non-abrasive or chloric solutions.

	7	=